



















## **ACCESSORIES:**

- a. Outdoor conversion kit
- b. Above waste bin option
- c. Floor cleaning kit for CNC's
- d. Quick Fit ducting kits/manifolds for all machinery brands
- e. From 2.2kW to 15kW options
- f. Discharge to Wheeliebins
- g. Variable Speed Drive (VSD)





T750 with optional

outdoor kit

- Modular design that delivers reliable extraction for today and in the future
- Compact yet powerful units using proven European filter and fan designs
- Quiet operation & high efficiency
- Over 400+ systems installed throughout Australasia in recent years



PROVEN, RELIABLE & POWERFUL PERFORMANCE FOR SMALL / MEDIUM APPLICATIONS

Airtight

## AVAILABLE IN 3 SIZES: T500-T1000

Airtight

The T-Series range of dust collectors are perfectly suited for your small to medium joinery, cabinet and kitchen making operation. It provides highly effective dust extraction for, typically, 3-5 machines including your CNCs, panel saws, and edgebanders.

The T-Series has the best performance/cost ratio of any dust collector in its market segment. The quiet operation and high performance of this system ensure superior results, unmatched by any in the industry.

The T-Series' superior performance and quality has been proven in more installations than any other brand and are the recommended system by all major woodworking machinery suppliers.

# T500

## 1750

# T1000

### **OUICK FACTS**


- 15m3, 16 needle-felt bags
- 1930W x 1270D x 3350H • Powerful & high performance
- 22.5m3, 24 needle-felt bags
- Dimensions 2515W x 1270D x 3350H
- Powerful & high performance
- 31-40m3, 32 needle-felt bags
- Dimensions:
- 3450W x 1270D x 3350H Powerful & high performance

## TECHNICAL PARAMETERS

- Fan 2880rpm, 4kW, 250 Ø inlet + incl. starter box
- 2 plastic waste bags
- Typical capacity: 4,500 m3/h (dependant on dust load & system pressure)
- Fan 2880rpm, 7.5kW, 315 Ø inlet + incl. starter box
- 3 plastic waste bags
- Typical capacity: 7,500 m3/h (dependant on dust load & system pressure)
- Fan 2880, 11-15kW, 400 Ø inlet + incl. starter box
- Variable Speed Drive (maximum power at lowest running cost!)
- Typical capacity 10,000m3/h (dependent of dust load & system pressure

\*Airtight is the preferred supplier for all major woodworking machinery suppliers in Australia/NZ. \*If height restrictions are in place, we can offer the S-Series filters which are more compact in size









**(** 



🔀 les@airtight.com.au



